


NEW LNG TRUCK



6x4 TRACTOR 10 WHEELS



วิ่งไกลกว่า 1,400 กม.ต่อการเติมแก๊ส 1 ครั้ง



น้ำหนักบรรทุกรวม : 50,500 กก.



เป็นมิตรกับสิ่งแวดล้อม

NEW LNG TRUCK 6x4 TRACTOR 10 WHEELS

Model	LZ4252H7DC1
Driver type	6X4
Chassis Dimensions	
Chassis Dimensions(L*W*H)	7390mm*2495mm*3330mm
Wheel base	3800+1350
Front/Rear wheel track	2080mm/1860mm
Front/Rear overhang	1525mm/715mm
vehicle weights	
G.C.W	50500kg
Maximum traction mass	41950kg
Curb weight	8550kg
Frame profile Dimensions	
Frame width	860mm
Section height	282mm
Section thickness	8mm
Engine	
Type	YC6K1342N-50
Emission level	Euro V Common Rail
Maximum power	309kW/1900rpm
Maximum torque	1800N.m/1100-1500rpm
Number of cylinders	6
Displacement	12.939L
Cylinder bore×Stroke	129×165mm
Clutch	
Plate's diameter	φ430mm
Operating system	Hydraulic control ,Pulling
Gear box	
Type	12JSD180TA (Aluminium)
Number of gears	12 forward gears& 2 reverse 12
Gear ratios	12,1,9.41,7.31,5.71,4.46,3.48,2.71,2.11,1.64,1.28,1.078; r1=11.56; r2=2.59;
Axle	
Front Axle	7.5T front axle, dram brake 7.5T Max payload 7.5t 7.5T
Rear Axle	shell with stamping and welding process , High payload performance, differential lock between axle and wheel , speed ratio:4.111 MAXpayload 2×10t
Suspension	
Front suspension	3-Leaf spring with stabilizer bar 3
Rear suspension	4-leaf spring with stabilizer bar 4
Battery	
Voltage	24V
Battery capacity	150Ah (2)
Fuel Tank	
Type	LNG tank
Capacity	1000L
Others	
Cab	H73R high roof two-bedroom cab (right rudder),Front mechanical rear airbag cab suspension, electro-hydraulic rollover, airbag shock driver seat, power doors and windows, WABCO brake valve, metal paint, fully enclosed shroud, multi-state switch, electromagnetic clutch fan, cruise control system, 50 # Saddle
Brake System	Full air brake system,split pneumatic circuit; parking spring brake acting on rear axles, exhaust brake, ABS(WABCO)
Saddle model	JOST brand 50
Tyres	295/80R22.5-18PR
Minimum turning circle	9m
Minimum ground clearance	264mm
Economical speed	60-80km/h
Maximum gradeability	≥25%